

ZT34J

TELESCOPIC BOOM LIFTS

Comply with CE/ANSI/GB Standard

HIGHLIGHTS

- Better work envelop performance, 10% larger than competitor.
- Zoomlion AWM Remote Monitoring and Rental Management System.
- Smart telematic control interface with self-diagnostic monitoring capability.
- Platform dual capacity design, up to 300/454 kg.
- Smooth & stable boom extension technique controls the minimum stable extending speed at 0.015 m/s.

FEATURES

Standard Features

Horn

All motion alarm

Proportional control

Self-closing entry gate

Flashing amber beacon

GPS positioning and tracking system

Remote monitoring and rental management system

Auto-leveling system

Emergency stop button

Over tilt protection system

Emergency descent system

On-board diagnostic system

Oscillating axle

4.3' LED display

Load sensing system

Swing-out engine tray

Accessories & Options

Platform work lights

Anti-collision device

AC power to platform



ZOOMLION

ZT34J - MAIN SPECS OF TELESCOPIC BOOM LIFTS

Comply with CE/ANSI/GB Standard

	Model	ZT34J	
SIZE	Work Height	36m	
	Platform Height	34m	
	Horizontal Outreach	23.50m	
	A - Stowed Length	13.50m	
	B - Stowed Width	2.49m	
	C - Stowed Height	3m	
	D - Platform Length	2.44m	
	E - Platform Width	0.91m	
	F - Wheelbase	3.80m	
	Wheelbase	2.05/3.41m	
	G - Ground Clearance	0.41m	
PERFORMANCE	Platform Capacity (Unrestricted/Restricted)	300/454kg	
	Drive Speed (Working)	5.5km/h	
	Gradeability	45%(24°)	
	Turning Radius (Inside)	2.80m	
	Turning Radius (Outside)	5.70m	
	Turntable Swing	360° continuous	
	Platform Rotation	±90°	
	Tail Swing	1.88m	
	Jib (Range of Articulation)	130°(-55°~75°)	
	Max. Working Slope	3°	
	Max. Wind Speed	12.5m/s	
	POWER	Engine	Kohler KDI2504TCR
		Fuel Tank Capacity	200L
Control Voltage		12V DC	
Hydraulic Tank Capacity		250L	
Drive Mode		4WD	
Steering Mode		Front-wheel/Rear-wheel/Crab	
TIRE	Type	IN445/50D710 Foam-filled Tires	
	WEIGHT	Gross 19200kg	

ZT34J Working Envelope

